

TF1 Sigma Filter Flushing Adapter 62453

- Fast, easy flushing with connection via the Fernox TF1 Sigma Filter
- Enables the full flow rate to optimise cleaning efficiency
- Allows the primary side of the secondary heat exchanger on combination boiler to be cleaned by simply turning on the domestic hot water tap to engage the boiler diverter valve
- Fernox TF1 Sigma Filter Flushing Adapter is rated to 85°C
- 0



This easy-to-use TF1 Sigma Flushing Adapter is designed to work in conjunction with the TF1 Sigma Filter as a fast and convenient way to connect a powerflushing machine to the system. By simply replacing the main body of the filter from the inlet/outlet manifold, the Adapter can be fitted to the unit. The Adapter also allows for quick and easy dosing via the drain valve of the TF1 Sigma Filter

Application

1. Drain the central heating system water.
2. Replace the TF1 Sigma Filter body with the TF1 Sigma Filter Flushing Adapter.
3. Connect the Fernox Powerflow Flushing Machine to the TF1 Sigma Filter Flushing Adapter. Use 3/4" BSP female nut liner and seals, as provided with the Fernox Powerflow Flushing Machine.

Package, Handling & Safety

Individually packaged with instructions included. No special storage requirements.

Specification

When used appropriately, the Fernox TF1 Sigma Filter Flushing Adapter is maintenance-free.

Single Item

Height mm 88
Width mm 74
Depth mm 65
Weight kg 0.106
Barcode EAN 5014551624535

Outer Carton

Outer Height mm 0
Outer Width mm 0
Outer Depth mm 0
Outer Weight kg 0.000
OCU Barcode N/A

Last modification 12-02-2021 (d/m/y)